

## 3M™ Gloss Wrap Overlamine 8418G

### Product Description

- 1.2 mil 3M cast vinyl film – thinner, but still has a great feel for managing panels
- Highly conformable for compound curves
- Gloss on par with Overlamine 8518 for wet-paint look
- Excellent clarity
- Lighter weight vs. Overlamine 8518
- Expected performance life of 6 years (unwarranted period applied to a flat, vertical, outdoor surface)

### Recommended Types of Graphics and End Uses

- Vehicle wraps
- Fleet/vehicle
- Watercraft
- Transit
- Labels

### Characteristics

These are typical values for unprocessed product. Processing may change the values.

### Performance Characteristics

Characteristic	Value
Material	Vinyl
Cast or non-Cast	Cast
Thickness	1.2 mils
Gloss	Gloss
Liner	Polyester
Lamination Temperature	50 to +100 °F (10 to +38 °C)
In Use Temperature Range	-65 to +200 °F (-54 to +93 °C) (not extended for periods of time at the extremes)
Chemical Resistance	<ul style="list-style-type: none"> <li>• Resists mild alkalis, mild acids, and salt</li> <li>• Excellent resistance to water (<i>does not include immersion</i>)</li> <li>• Resists occasional fuel spills</li> </ul>
Flammability	ASTM E84 report: go to the On-line Product Catalog at <a href="http://3M.com/graphics">3M.com/graphics</a> All other test reports: call 1-800-328-3908

### Warranty Information

All 3M graphic protection products are covered by the 3M Basic Product Warranty.

A warranty period may be offered based on the graphic construction and application details. Always refer to the 3M Product Bulletin for the 3M base film or flexible substrate you are using to determine if the graphic protection product you want to use is recommended and what, if any warranty period is offered.

#### IMPORTANT NOTE

Warranty information including limitations and exceptions and warranty periods for this product can be found at [3M.com/graphicswarranties](http://3M.com/graphicswarranties).

#### Quick Links

- [3M Graphics Warranties](#)
- [Technical Information Selector](#)
- [Safety Data Sheets \(SDS\)](#)
- [Flammability](#)
- [Videos](#)

Some of these links lead to web-based resources that are not product-specific.



## Warranty Coverage Overview

The warranty coverage for eligible graphics is based on the user both reading and following all applicable and current 3M Graphics Product and Instruction Bulletins. The warranty period for eligible graphics is as follows:

Base Film + 8418G	MCS Coverage		Product Guarantee Coverage	
	Vehicle	Boat	Vehicle	Boat
IJ175Cv3 IJ180Cv3 IJ180C IJ180-10 IJ180mC-10 IJ180mC-114 IJ180mC-120 SV480mC LX480mC	5 years	2 years	3 years	2 years

Additional information can be found at [3M.com/graphicswarranties](http://3M.com/graphicswarranties).

- [3M Graphics Warranties Bulletin](#)
  - This bulletin contains information on limitations and exceptions, and warranty period reductions for 3M Graphics Warranties. The warranty period may be reduced and stipulations may apply for certain constructions, applications, and graphic exposures as covered in this Bulletin.
- [3M Graphics Warranties Selector](#)
  - Use this selector to search for your vertical warranty period by product type, ink type, film name, and/or ink/printer platform.
- [U.S. Desert Southwest Region Map](#)
  - Use this map of hot, arid desert areas to determine if you are subject to reduced warranted durabilities.

The warranties set forth in this Bulletin are made in lieu of all other express or implied warranties, including any implied warranty of merchantability, fitness for a particular purpose, or arising out of a course of dealing, custom, or usage of trade.

## 3M Basic Product Warranty

3M Graphics Products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the specifications stated in its applicable 3M Graphics Product Bulletin and as further set forth in the [3M Graphics Warranties Bulletin](#).

## Limited Remedy

The limited remedy applicable to each warranty is addressed in the 3M Graphics Warranties Bulletin found at [3M.com/graphicswarranties](http://3M.com/graphicswarranties).

## Limitation of Liability

Except to the extent prohibited by law, 3M SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE TO PURCHASER OR USER FOR ANY DIRECT (EXCEPT FOR THE LIMITED REMEDY PROVIDED HEREIN), INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, LABOR, NON-3M MATERIAL CHARGES, LOSS OF PROFITS, REVENUE, BUSINESS, OPPORTUNITY, OR GOODWILL) RESULTING FROM OR IN ANY WAY RELATED TO 3M'S GRAPHICS PRODUCTS, SERVICES, OR THIS BULLETIN. This limitation of liability applies regardless of the legal or equitable theory under which such losses or damages are sought.

## Health and Safety

### CAUTION

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to [3M.com/SDS](http://3M.com/SDS), or by mail or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturer's instructions for safe operation.

## Air Quality Regulations

State Volatile Organic Compound (VOC) regulations may prohibit the use of certain chemicals with VOC's in graphic arts coatings and printing operations. For example, the California South Coast Air Quality Management District prohibits use of certain solvent-based solutions without a permit and other California AQMD's prohibit use of certain solutions without a permit or regulatory exemption. Check with your State environmental authorities to determine whether use of this solution may be restricted or prohibited.

## Factors that Affect Graphic Performance Life

The actual performance life of a graphic is affected by:

- the combinations of graphics materials used.
- complete ink drying or curing.
- selection, condition and preparation of the substrate.
- surface texture.
- application methods.
- angle and direction of sun exposure.
- environmental conditions.
- cleaning or maintenance methods.

## Graphics Manufacturing

### CAUTION

Before using any equipment, always read the manufacturer's instructions for safe operation.

### Completely Dry Graphics

### IMPORTANT NOTE

Incomplete drying or curing can result in graphic failure including curling, increased shrinkage and adhesion failure, which are not covered under any 3M Graphic Warranty.

See the ink's 3M Product and Instruction Bulletin for more details.

## Application and Installation

In addition to other 3M Bulletins specified in this document, the following Bulletins provide details that you may need to successfully apply a graphic.

- [3M Instruction Bulletin 4.22](#) Lamination Basics for Inkjet Printed Graphics

## Maintenance and Cleaning

Use a cleaner designed for high-quality painted surfaces. The cleaner must be wet, non-abrasive, without solvents, and have a pH value between 3 and 11 (neither strongly acidic nor strongly alkaline). See [3M Instruction Bulletin 6.5](#) for details.

## Shelf Life, Storage and Shipping

### Shelf Life

The shelf life is **never more than 3 years** from the date of manufacture on the original box.

If you process the film, the shelf life is changed to **1 year** from the processing date, but not later than the 3 year maximum from the manufacturing date.

### Storage Conditions

- 40° to 100°F (4° to 38°C)
- Out of sunlight
- Clean, dry area
- Original container
- Bring the film to print room temperature before using

### Shipping Finished Graphics

Flat, or rolled printed side out on 5 inch (13 cm) or larger core. This helps prevent the liner, and, if used, the application tape from popping off.

#### Commercial Solutions

3M Center, Building 220-12E-04  
St. Paul, MN 55144

1-800-328-3908  
3M.com/Graphics

© 3M 2018. All rights reserved.

3M and MCS are trademarks of 3M. Used under license in Canada.  
All other trademarks are property of their respective owners.  
Revision A, March 2018 Please recycle.

