

# WOW II ECO

## Channel Letter Solution

New ECONOMIC generation of WOW II modules, boasts of high efficiency at 165lm/w, which can achieve light output up to 165 lumens per module.



- UV and IR Protected
- L80 rating of 50,000 hours
- Designed for medium to large Channel letters
- Double face tape and mechanical mounting options



## Specification Chart

Product Options	WOWII White (7500K/6300K/2700K)	WOW II Red	WOW II Green	WOW II Blue
Input Voltage	12VDC			
Beam Angle	170°			
Power consumption ( watts )	1w/mod	0.5w/mod	0.72w/mod	0.72w/mod
LED / module	2			
Modules / foot	1.5/ft. fully stretched			
Lumen / module	165lm	13lm	36lm	13lm
Lumen / foot	247.5lm	19.5lm	54lm	19.5lm
Protection Grade	IP67			
Operating Temp	-40°~ +60 °C / -40° ~ +140 °F			
Storage Temp	-40°~ -70 °C / -40° ~ +158 °F			
Cascade	25 mods single-ended power feed , 50 mods double-ended power feed			
Packaging	40pcs/chain, 80pcs/bag, 10 bags/outer carton			

## Modules Population Guide

Channel Depth (in)	Multiple rows (rows spacing)	Single rows
3"	6"	
4"	9"	
5" - 6"	12"	
7" - 10"	18"	

## Dimension

